LIQUID SEAI Fabric-To-Frame Adhesive













Shown with optional applicator squeeze bottle

Applying Liquid Seal to bond fabric to frame. Mesh is stretched on AWT's Stretch-Lok™ manual screen stretching system.

ADVANTAGES

- Fast Drying—Liquid Seal bonds fabric to frame and dries in minutes
- Water- and solvent-resistant—Use Liquid Seal with all fabrics, frames, and most screen printing solvents
- Flexible and Strong—Stretch four or five layers of mesh on a frame before removing it with Solvent TH-660™
- **Extended Shelf Life**—The shelf life of mixed Liquid Seal can be extended for approximately two weeks
- **Non-irritating**—Contains no skin irritants which could affect operators

AWT's Liquid Seal™ is a flexible and strong adhesive product with multiple applications in your screen making department. Liquid Seal bonds all fabrics to any wooden, metal or plastic frame.

Extend the life of your wooden frame by brushing or dipping the frame and completely covering the wood with Liquid Seal to waterproof the wood and eliminate warping.

Use Liquid Seal as a permanent blockout. Liquid Seal can be heat sealed and used as a laminating adhesive for most plastics.



4321 N. Knox Ave., Chicago IL, 60641





sales@awtworldtrade.com





773.777.0909

LIQUID SEAL

Fabric-To-Frame Adhesive

Product Information

AWT's Liquid Seal is a strong and flexible adhesive product with multiple applications in your screen making department. Liquid Seal can be used to affix fabric to frames; to seal wood frames; to block out screens; and to eliminate ink seepage. Also suitable for use as a heat-sealable laminating adhesive for most plastics.

Liquid Seal is not affected by most screen printing solvents and can be used with all types of frames and mesh. AWT offers a range of optional products and accessories for use with Liquid Seal, including Solvent TH-660, squeeze applicator bottles, and plastic spreaders/scrapers.

AWT CARRIES A COMPLETE LINE OF FRAME-STRETCHING SYSTEMS



Shown with optional applicator squeeze bottles/spreaders

Specifications

| CATALOG # | DESCRIPTION |
|------------|--|
| LS-535Q | Liquid Seal™ Quart with 2 oz. catalyst |
| LS-535G | Liquid Seal™ Gallon with 8 oz. catalyst |
| LS-5355G | Liquid Seal™ 5-Gallon Can with catalyst |
| LS-53555G | Liquid Seal™ 55-Gallon Drum with catalyst |
| LSC5368-0Z | Catalyst, 8 oz extra |
| TH-660Q | Solvent TH-660 - Quart |
| TH-660G | Solvent TH-660 - Gallon |
| SB-1216 | 16 oz applicator squeeze bottle with spout & cap for applying Liquid Seal (package of 12 bottles) |
| SB-1216S | 16 oz applicator squeeze bottle with spout & cap for applying Liquid Seal (Each) |
| PS-04 | 4" Square plastic polyethylene spreader / scraper square edge - Pkg. of 12 |
| PS-04S | 4" Square plastic polyethylene spreader / scraper square edge - each |
| PS-06 | 6" Square plastic polyethylene spreader / scraper square edge - Pkg. of 12 |
| PS-06S | 6" Square plastic polyethylene spreader / scraper square edge - each |
| PS-12 | 12" Square plastic polyethylene spreader / scraper square edge - Pkg. of 12 |
| PS-12S | 12" Square plastic polyethylene spreader / scraper square edge - each |

IMPORTANT NOTE: SAFETY CLOTHING AND GLOVES SHOULD BE WORN DURING APPLICATION.

A Company with proven experience.



sales@awtworldtrade.com



www.awt-gpi.com



773.777.7100



773.777.0909

Products you can trust.